



INLINE FILTERS



INLINE WATER FILTER For Taste and Odor Removal	
Service Life	3000 Gallons
Flow Rate	1 GPM (3.8 LPM)
Temperature Range	40 to 100 F (4.4 to 38.8 C)
Pressure Range	20 to 125 PSI (1.4 to 8.6 bar)

Do not use with water that is microbiologically unsafe or contains naturally occurring radon.
Aquamor filters are not intended to remove pharmaceuticals.
Aquamor filters are not intended to remove lead.

In a “nutshell” our Inline Water Filters are among the highest quality water filters you can buy today. Our inline filters are produced using the best available materials and with an unparalleled attention to quality. The result is superior products having high capacities for a wide range of applications.

We look closely at things other companies are not even discussing. Things like extraction testing on a lot basis to ensure that our carbons are not adding anything undesirable back into the water. Ensuring that the fit, finish and color of our products is consistent and appealing. There is also 100% quality testing on every filter before it leaves the factory.

TST Inline filters are constructed from the highest quality carbons and specially selected plastics and proprietary media to give our customers some of the best performing filters in the industry. All materials comply with and/or have been tested to NSF Standard 42.

Use TST inline Water Filters in all your POU and Reverse Osmosis applications..

PRODUCT FEATURES

- 100% Factory Leak Tested
- Assembled or Made in the USA
- NSF42 Listed GAC Carbon
- All Materials Used Are NSF Approved or FDA Compliant
- High Capacity/ Low Pressure Drop
- John Guest® Openings Available

OPTIONS

- Private Labeling
- Multi-media Fills
- Custom Media Fills
- Custom Packaging



Aquamor, LLC
42188 Rio Nedo
Temecula, CA 92590

(951) 541-9517
(951) 296-1050 Fax

www.aquamorusa.com
info@aquamorusa.com

PART #	SIZE	MEDIA	RATED OPENING	CAPACITY†
Coconut Shell GAC				
IN0611-1	2" x 6"	Coconut Shell GAC	1/4" FPT	750
IN0611-2	2" x 6"	Coconut Shell GAC	1/4" FQC	750
KDF				
IN0612-1	2" x 6"	Coconut Shell GAC / KDF 55 (.25lb)	1/4" FPT	3,000
IN0612-2	2" x 6"	Coconut Shell GAC / KDF 55 (.25lb)	1/4" FQC	3,000
Scale Control				
IN0613-1	2" x 6"	Coconut Shell GAC / Phosphate (1oz)	1/4" FPT	500
IN0613-2	2" x 6"	Coconut Shell GAC / Phosphate (1oz)	1/4" FQC	500
Coconutshell GAC				
IN1011-1	2" x 10"	Coconut Shell GAC - NSF Certified	1/4" FPT	3,000
IN1011-2	2" x 10"	Coconut Shell GAC - NSF Certified	1/4" FQC	3,000
Sediment				
IN1015-1	2" x 10"	5 Micron Spun Bonded Polypropylene - NSF Certified	1/4" FPT	N/A*
IN1015-2	2" x 10"	5 Micron Spun Bonded Polypropylene - NSF Certified	1/4" FQC	N/A*
Scale Control‡				
IN1013-1	2" x 10"	Coconut Shell GAC / Phosphate (2oz) - NSF Certified	1/4" FPT	1,500
IN1013-2	2" x 10"	Coconut Shell GAC / Phosphate (2oz) - NSF Certified	1/4" FQC	1,500
IN1024-1	2" x 10"	Coconut Shell GAC / Phosphate (8oz)	1/4" FPT	1,000
IN1024-2	2" x 10"	Coconut Shell GAC / Phosphate (8oz)	1/4" FQC	1,000
IN1017-1	2" x 10"	Phosphate (16oz)	1/4" FPT	6 months
IN1017-2	2" x 10"	Phosphate (16oz)	1/4" FQC	6 months
IN1016-1	2" x 10"	Coconut Shell GAC / Phosphate (2oz) / KDF 55 (.50lb)	1/4" FPT	6,000
IN1016-2	2" x 10"	Coconut Shell GAC / Phosphate (2oz) / KDF 55 (.50lb)	1/4" FQC	6,000
IN1018-1	2" x 10"	Cation Softening Resin	1/4" FPT	N/A*
IN1018-2	2" x 10"	Cation Softening Resin	1/4" FQC	N/A*
KDF-55				
IN1027-1	2" x 10"	Coconut Shell GAC / KDF 55 (.25lb)	1/4" FPT	4,500
IN1027-2	2" x 10"	Coconut Shell GAC / KDF 55 (.25lb)	1/4" FQC	4,500
IN1012-1	2" x 10"	Coconut Shell GAC / KDF 55 (.50lb)	1/4" FPT	9,000
IN1012-2	2" x 10"	Coconut Shell GAC / KDF 55 (.50lb)	1/4" FQC	9,000
IN1028-1	2" x 10"	Coconut Shell GAC / KDF 55 (.75lb)	1/4" FPT	13,000
IN1028-2	2" x 10"	Coconut Shell GAC / KDF 55 (.75lb)	1/4" FQC	13,000
IN1029-1	2" x 10"	Coconut Shell GAC / KDF 55 (1.00lb)	1/4" FPT	17,500
IN1029-2	2" x 10"	Coconut Shell GAC / KDF 55 (1.00lb)	1/4" FQC	17,500
Remineralization				
IN1014-1	2" x 10"	Coconut Shell GAC / Calcite	1/4" FPT	1,500
IN1014-2	2" x 10"	Coconut Shell GAC / Calcite	1/4" FQC	1,500
Carbon Block				
IN1019-1	2" x 10"	5 Micron Compression Molded Carbon Block	1/4" FPT	3,000
IN1019-2	2" x 10"	5 Micron Compression Molded Carbon Block	1/4" FQC	3,000
IN1020-1	2" x 10"	1 Micron Compression Molded Carbon Block	1/4" FPT	3,000
IN1020-2	2" x 10"	1 Micron Compression Molded Carbon Block	1/4" FQC	3,000
IN1021-1	2" x 10"	1 Micron Compression Molded Carbon Block With Lead Scavenger	1/4" FPT	1,250
IN1021-2	2" x 10"	1 Micron Compression Molded Carbon Block With Lead Scavenger	1/4" FQC	1,250
Silver Impregnated Coconutshell GAC				
IN1025-1	2" x 10"	0.2% Silver Impregnated Coconut Shell GAC	1/4" FPT	3,000
IN1025-2	2" x 10"	0.2% Silver Impregnated Coconut Shell GAC	1/4" FQC	3,000
IN1023-1	2" x 10"	0.2% Silver Impregnated Coconut Shell GAC / KDF 55 (.50lb)	1/4" FPT	9,000
IN1023-2	2" x 10"	0.2% Silver Impregnated Coconut Shell GAC / KDF 55 (.50lb)	1/4" FQC	9,000
Mixed Bed DI Resin - Semi Conductor Grade				
IN1025-1	2" x 10"	Mixed Bed DI Resin	1/4" FPT	N/A*
IN1025-2	2" x 10"	Mixed Bed DI Resin	1/4" FQC	N/A*
IN1026-1	2" x 10"	Color Changing DI Resin Clear Body Inline	1/4" FPT	N/A*
IN1026-2	2" x 10"	Color Changing DI Resin Clear Body Inline	1/4" FQC	N/A*

†Rated capacities are based on manufacturer's internal test data and third party lab results. Actual capacity may vary.

‡Phosphate is sequesterant that is designed to dissolve over a 6 month period. Phosphate filters should be changed every 6 months.

*The effective life of sediment filters and ion exchange resins is dependant on water quality.

Warning - Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

All filters contain very fine particles (fines) which must be flushed from the filter prior to use.
After installation, it is important that you flush the filter for 30 seconds before putting into service.



Aquamor, LLC
42188 Rio Nedo
Temecula, CA 92590

(951) 541-9517
(951) 296-1050 Fax

www.aquamorusa.com
info@aquamorusa.com